

FROG® PHOS REMOVER 4PRO™ DFU

BEFORE APPLYING FROG PHOSPHATE REMOVER 4PRO:

Make sure all pool equipment is working properly, including pump, filter, skimmer and heater. If recently used FROG® Algae Blocker 4Pro™, wait at least 2 weeks before using FROG Phosphate Remover 4Pro.

Curative

Removal: 1,000 ppb or 1 ppm of phosphate.

1. Backwash or clean filter according to manufacturer's instructions.
2. Using chart – Apply appropriate number of pods to the skimmer or pump basket. No more than 3 pods in pump basket at once.
3. Allow pump and filter to run continuously for 24-48 hours.
4. Don't backwash filter for 2 weeks after application. Pools less than 7,500 gallons – be prepared for excessive clouding and flocculation of the pool.

NOTE: If high levels of phosphates are present when you first use this product, the pool may become cloudy; particulates may drop to the bottom of the pool and should be vacuumed out. Continue to run the pump for 72 hours and backwash or clean the filter if the pressure increases 8-10 psi. Once pool water is clear, to maintain sparkling water, we recommend using FROG Clarifier 4Pro™ (a pool clarifier) to help give the pool that extra sparkle.

Preventative

Control the pool's phosphate levels all year long!

1. Backwash or clean filter according to manufacturer's instructions.
2. Add 1 pod per 30,000 gallons to the skimmer or pump basket.
3. Allow pump and filter to run continuously for 24-48 hours.
4. Don't backwash filter for 2 weeks after application.
5. Apply a new pod every month to prevent phosphate build-up.

POOL SIZING CHART FOR REMOVING PHOSPHATES	
Gallons	# of Pods
7,500 – 10,000	1
10,001 – 20,000	2
20,001 – 30,000	3